



# MATERIAL SAFETY DATA SHEET

## PROSALL GRAF TECH

1. Product And Company Identification	
<b>Supplier</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  <b>Company Contact:</b> Aludia B. Hernandez <b>Telephone Number:</b> 708-865-1000 <b>FAX Number:</b> 708-865-0923 <b>E-Mail:</b> sales@chaseproducts.com <b>Web Site:</b> www.chaseproducts.com	<b>Manufacturer</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  <b>Company Contact:</b> Aludia B. Hernandez <b>Telephone Number:</b> 708-865-1000 <b>FAX Number:</b> 708-865-0923 <b>E-Mail:</b> sales@chaseproducts.com <b>Web Site:</b> www.chaseproducts.com
<b>Supplier Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924	<b>Manufacturer Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924
<b>Issue Date:</b> 09/06/2005  <b>Product Name:</b> PROSALL GRAF TECH <b>Chemical Name:</b> 7-7785 <b>CAS Number:</b> Not Established <b>MSDS Number:</b> 3393 <b>Product Code:</b> 433-1105-1 <b>Product/Material Uses</b> - Vandal Mark Remover	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
1,2,4-TRIMETHYLBENZENE	95-63-6		20 - 25
ALKANOLAMIDE	68603-42-9		
BUTANE	106-97-8		
CUMENE	98-82-8		1 - 5
D-LIMONENE	5989-27-5		
ETHOXYLATED ALCOHOL	68002-97-1		
ETHYL ALCOHOL	64-17-5		
PINE OIL	8002-09-3		
PROPANE	74-98-6		
TRIMETHYLBENZENE (MIXED ISOMERS)	25551-13-7		
XYLENE (MIXED ISOMERS)	1330-20-7		1 - 5
<b>NOTE:</b> Trimethylbenzenes, Cumene, Xylene and 1,2,4-trimethylbenzene are from Light Aromatic Solvent Naphtha (CAS# 64742-95-6). Hazardous components, according to OSHA, are listed when present at 1.0% or greater. Carcinogens are listed when present at 0.1% or greater.			

3. Hazards Identification
<b>Primary Routes(s) Of Entry</b> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. <b>Eye Hazards</b> - Irritant to eyes. <b>Skin Hazards</b> - Irritant to skin. <b>Ingestion Hazards</b> - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if

# MATERIAL SAFETY DATA SHEET

## PROSALL GRAF TECH

### 3. Hazards Identification - Continued

swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately.

**Inhalation Hazards** - Deliberate inhalation of concentrate vapor or mist may cause headaches, dizziness and nausea.

**Chronic/Carcinogenicity Effects** - Over exposure to petroleum solvents have been associated with nervous system damage.

**Teratogenicity (Birth Defects)** - Not known.

**Reproductive Effects** - Not known.

**Neurotoxicity** - Not known.


**Mutagenicity (Genetic Effect)** - Not known.

**Signs And Symptoms** - Acute: Deliberate inhalation of concentrate vapor or mist may cause headaches, dizziness and nausea. Contact with skin can cause irritation. Irritant to the eyes.

**Conditions Aggravated By Exposure** - May aggravate pre-existing skin, eye and respiratory disorders.

**Conditions Aggravated By Overexposure** - May aggravate pre-existing skin, eye and respiratory disorders.

### First Aid (Pictograms)



### 4. First Aid Measures

**Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**Skin** - Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

**Ingestion** - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

**Inhalation** - If overcome by vapor move victim to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

### 5. Fire Fighting Measures

**Flash Point:** Not available °F Not available °C

**Flash Point Method:** Not available

**Lower Explosive Limit:** Not available

**Upper Explosive Limit:** Not available

**Fire And Explosion Hazards** - This product is an aerosol product for which **Flame Projection is over 18 in. with flashback.** Temperatures above 120 F may cause cans to burst.

**Extinguishing Media** - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

**Fire Fighting Instructions** - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

### 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

### Handling & Storage (Pictograms)



# MATERIAL SAFETY DATA SHEET

## PROSALL GRAF TECH

### 7. Handling And Storage

**Handling And Storage Precautions** - Store in a cool, dry place away from heat and open flame.

**Handling Precautions** - Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.

**Storage Precautions** - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B)**

**Work/Hygienic Practices** - Wash hands thoroughly after using this product.

### Protective Clothing (Pictograms)



### 8. Exposure Controls/Personal Protection

**Engineering Controls** - Use with adequate general and local exhaust ventilation.

**Eye/Face Protection** - Conventional eyeglasses to guard against splashing.

**Skin Protection** - Nitrile rubber gloves required.

**Respiratory Protection** - Use in well-ventilated area ONLY. NIOSH-approved respirator recommended. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear and appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

#### Ingredient(s) - Exposure Limits

BUTANE

ACGIH TLV-TWA 800 ppm

CUMENE

ACGIH TLV-TWA 50 ppm ; OSHA PEL-TWA 50 ppm (Skin)

ETHYL ALCOHOL

ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1000 ppm

PROPANE

ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm

TRIMETHYLBENZENE (MIXED ISOMERS)

ACGIH TLV-TWA 25 ppm

XYLENE (MIXED ISOMERS)

ACGIH TLV-STEL 150 ppm ; ACGIH TLV-TWA 100 ppm ; OSHA PEL-TWA 100 ppm

### 9. Physical And Chemical Properties

**Appearance** - Green, yellowish, viscous liquid.

**Odor** - Pine odor.

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** Not applicable °F Not applicable °C

**Boiling Point:** Light Aromatic Solvent Naphtha 308-335 °F 160.83 °C

**Specific Gravity:** 0.895 concentrate

**Percent VOCs:** 94.52

**pH Factor:** NA

**Solubility:** Insoluble

**Evaporation Rate:** Faster than butyl acetate

# MATERIAL SAFETY DATA SHEET

## PROSALL GRAF TECH

### 9. Physical And Chemical Properties - Continued

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

**Conditions To Avoid (Stability)** - Temperatures above 120 F

**Incompatible Materials** - Avoid heat, open flame and contact with strong oxidizers, nitric acid and sulfuric acid.

**Hazardous Decomposition Products** - Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

**Conditions To Avoid (Polymerization)** - Temperatures above 120 F

### 11. Toxicological Information

No Data Available...

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** Place in trash or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

### 14. Transport Information

**Proper Shipping Name** - ORM-D Consumer Commodity

**Hazard Class**

2.1

**DOT Identification Number**

UN1950

**DOT Shipping Label**

Aerosol Consumer Commodity

### 15. Regulatory Information

**U.S. Regulatory Information** - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**SARA Hazard Classes**

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

**SARA Section 313 Notification** - This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material: Cumene, Xylene and 1,2,4-trimethylbenzene. See Section 2 for % amounts in the product.

**Ingredient(s) - U.S. Regulatory Information**

1,2,4-TRIMETHYLBENZENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

CUMENE

# MATERIAL SAFETY DATA SHEET

## PROSALL GRAF TECH

### 15. Regulatory Information - Continued

#### Ingredient(s) - U.S. Regulatory Information - Continued

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

XYLENE (MIXED ISOMERS)

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

#### Ingredient(s) - State Regulations

1,2,4-TRIMETHYLBENZENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

CUMENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

ETHYL ALCOHOL

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

PINE OIL

New Jersey - Workplace Hazard; New York City - Hazardous Substance

PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance


TRIMETHYLBENZENE (MIXED ISOMERS)

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

XYLENE (MIXED ISOMERS)

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### NFPA



#### HMIS

HEALTH	*2
FLAMMABILITY	4
REACTIVITY	1
PERSONAL PROTECTION	B

### 16. Other Information

No Data Available...

# MATERIAL SAFETY DATA SHEET

## PROSALL GRAF TECH

### 16. Other Information - Continued

#### Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supersedes A Previous MSDS Dated: 09/21/2004

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Chase Products Co.

Printed Using MSDS Generator™ 2000