



Issue date 09-Dec-2020

# Safety Data Sheet

Version 3

## 1. Identification of the Substance/Preparation and of the Company/Undertaking

### Product Identifier

**Product name** CHAMPION SPRAYON CARPET & UPHOLSTERY FOAMING CLEANER  
**Chemical name** 7-7976-4

### Other means of identification

**Product code** FG 438-5148-11  
**Synonyms** Carpet and upholstery cleaner

### Recommended use of the chemical and restrictions on use

**Recommended Use** Carpets and upholstered surfaces.  
**Uses advised against** DO NOT USE ON FLOORS

### Details of the supplier of the safety data sheet

**Supplier Address** Chase Products Co.  
2727 Gardner Road  
Broadview, IL 60155  
708-865-1000  
**Manufacturer Address** Chase Products Co.  
2727 Gardner Road  
Broadview, IL 60155  
708-865-1000

### Emergency Telephone Number

**Company Phone Number** 708-865-1000  
**24 Hour Emergency Phone Number** 1-800-255-3924  
**Emergency telephone** ChemTel 1-800-255-3924

## 2. Hazards Identification

### Classification


FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

### Label Elements

### EMERGENCY OVERVIEW

**DANGER**

EXTREMELY FLAMMABLE AEROSOL  
Contains gas under pressure; may explode if heated



**Appearance** Cloudy, light yellow liquid      **Physical State** Aerosol      **Odor** Clean, floral

### Precautionary Statements - Prevention

Keep away from heat, sparks, open flames and hot surfaces. — No smoking  
Pressurized container: Do not pierce or burn, even after use

## FG 438-5148-11 CHAMPION SPRAYON CARPET & UPHOLSTERY FOAMING CLEANER

Do not spray on an open flame or other ignition source

### Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place  
Do not expose to temperatures exceeding 122 °F (50 °C)

### Hazards not otherwise classified (HNOC)

#### Other Information

- Harmful to aquatic life with long lasting effects
  - Harmful to aquatic life
- 0% of this mixture consist of ingredient(s) of unknown toxicity.

## 3. Composition/information on Ingredients

<b>Common Name</b>	Carpet and upholstery cleaner.
<b>Synonyms</b>	Carpet and upholstery cleaner.
<b>Chemical Family</b>	MIXTURES.
<b>Formula</b>	7-7976-4
<b>Chemical nature</b>	Aqueous solution of surfactants and cleaners.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	85-90	*
N-Butane	106-97-8	1-5	*
Sodium Lauryl Sulfate	151-21-3	1-5	*
Propane	74-98-6	1-5	*
2-Butoxyethanol	111-76-2	<1	*
Sodium Lauroyl Sarcosinate	137-16-6	<1	*

Chemical Additions Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

### FIRST AID MEASURES

<b>Eye Contact</b>	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.
<b>Inhalation</b>	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.
<b>Ingestion</b>	Ingestion from an aerosol product is unlikely to occur.
<b>Most important symptoms and effects, both acute and delayed</b>	
<b>Symptoms</b>	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation. Chronic: 2-butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney damage.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** None needed.

## 5. Fire-fighting measures

### Suitable extinguishing media

Dry chemical, CO2 or water spray.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

**Hazardous combustion products** Thermal decomposition may release carbon monoxide and carbon dioxide.

### Explosion data

**Sensitivity to Mechanical Impact** Contents under pressure, keep away from heat and open flame.

**Sensitivity to Static Discharge** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use with adequate general or local exhaust ventilation.

**For emergency responders** Remove all sources of ignition.

### Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

### Methods and material for containment and cleaning up

**Methods for Containment** Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

**Methods for cleaning up** Clean contaminated surface thoroughly.

## 7. Handling and Storage

### Precautions for safe handling

**Advice on safe handling** Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Store in a cool, dry place away from heat and open flame. Keep out of reach of children.  
**AEROSOL STORAGE LEVEL I (NFPA-30B) .**

**Incompatible Materials** Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.

## 8. Exposure Controls/Personal Protection

### Control parameters

**Exposure guidelines** See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Butane 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering controls** Use with adequate general or local exhaust ventilation.

**Individual protection measures, such as personal protective equipment**

**Eye/face Protection** Conventional eyeglasses to guard against splashing.

**Skin and Body Protection** Rubber, vinyl or household type gloves required.

**Respiratory protection** Use in a well-ventilated area ONLY. **WHEN USING INDOORS, KEEP WINDOWS AND DOORS OPEN UNTIL FUMES DISSIPATE.**

**General hygiene considerations** Wash hands thoroughly after handling.

**9. Physical and Chemical Properties**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Aerosol	<b>Odor</b>	Clean, floral
<b>Appearance</b>	Cloudy, light yellow liquid	<b>Odor threshold</b>	No information available
<b>Color</b>	light yellow		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>	9.48	No information available	
<b>Melting point/freezing point</b>	Not applicable	No information available	
<b>Boiling point/boiling range</b>	Water 212 °F/100 °C	No information available	
<b>Flash Point</b>	Not applicable. This is an foam aerosol that when tested for flammability the flame duration is 7 seconds or more and the flame height is 4 cm or more.	No information available	
<b>Evaporation Rate</b>	Faster than butyl acetate	No information available	
<b>Flammability (solid, gas)</b>		No information available	
<b>Flammability Limits in Air</b>		No information available	
<b>Upper flammability limits</b>	Not available		
<b>Lower Flammability Limit</b>	Not available		
<b>Vapor pressure</b>		No information available	
<b>Vapor Density</b>		No information available	
<b>Relative Density</b>	1.00 concentrate	No information available	
<b>Water solubility</b>		Soluble in water	
<b>Solubility in other solvents</b>		No information available	
<b>Partition coefficient</b>		No information available	
<b>Autoignition Temperature</b>		No information available	
<b>Decomposition temperature</b>		No information available	
<b>Kinematic viscosity</b>		No information available	
<b>Dynamic viscosity</b>		No information available	
<b>Explosive properties</b>	No information available		

**Oxidizing properties** No information available

**Other Information**

**Softening point** No information available  
**Molecular weight** No information available  
**VOC content (%)** 4.96  
**Density** 8.33 lb/gal  
**Bulk Density** No information available

**10. Stability and Reactivity**

**Reactivity**  
 Not applicable Not applicable

**Chemical stability**  
 Stable.

**Possibility of hazardous reactions**  
 Temperatures above 130 °F may cause cans to burst with force.

**hazardous polymerization** Hazardous polymerization does not occur.

**Conditions to Avoid**  
 Temperatures above 122 °F (50 °C).

**Incompatible Materials**  
 Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.

**Hazardous decomposition products**  
 Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

**11. Toxicological Information**

**Information on likely routes of exposure**

**Product Information** This product has not been tested as whole. See below for information on ingredients.

**Inhalation** Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.

**Eye Contact** Can cause irritation after contact with eyes.

**Skin contact** May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may results on skin absorption of potentially harmful amounts.

**Ingestion** This is an aerosol product, ingestion is unlikely to occur. 2-Butoxyethanol may cause red blood cell hemolysis and possible liver and kidney damage.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg ( Rat )	-	-
N-Butane 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h
Sodium Lauryl Sulfate 151-21-3	= 1288 mg/kg ( Rat )	= 200 mg/kg ( Rabbit )	> 3900 mg/m <sup>3</sup> ( Rat ) 1 h
Propane 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min
2-Butoxyethanol 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h = 486 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may results on skin absorption of potentially harmful amounts.

**Serious eye damage/eye irritation** Irritating to eyes.

**corrosivity** Not applicable.

**sensitization** No a skin sensitizer.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** Not known chronic effects based on available data. None of the ingredients present in excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Chemical name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3		

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration Hazard** Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.

**Numerical measures of toxicity - Product Information**

**Unknown acute toxicity** 0% of this mixture consist of ingredient(s) of unknown toxicity.

**The following values are calculated based on chapter 3.1 of the GHS document**

- ATEmix (oral)** 45231 mg/kg
- ATEmix (dermal)** 26852 mg/kg
- ATEmix (inhalation-gas)** 7402695 mg/l
- ATEmix (inhalation-dust/mist)** 45.1 mg/l
- ATEmix (inhalation-vapor)** 15076 mg/l

**12. Ecological Information**

**ecotoxicity**

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Sodium Lauryl Sulfate 151-21-3	53: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50 3.59 - 15.6: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static 30 - 100: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 117: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50	4.62: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 8 - 12.5: 96 h <i>Pimephales promelas</i> mg/L LC50 static 13.5 - 18.3: 96 h <i>Poecilia reticulata</i> mg/L LC50 semi-static 9.9 - 20.1: 96 h <i>Brachydanio rerio</i> mg/L LC50 semi-static 4.3 - 8.5: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 4.5: 96 h <i>Lepomis macrochirus</i> mg/L LC50 10.8 - 16.6: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 15 - 18.9: 96 h <i>Pimephales promelas</i> mg/L LC50 static 6.2 - 9.6: 96 h <i>Pimephales promelas</i> mg/L LC50 1.31: 96 h <i>Cyprinus</i>		1.8: 48 h <i>Daphnia magna</i> mg/L EC50

		carpio mg/L LC50 semi-static 5.8 - 7.5: 96 h Pimephales promelas mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 10.2 - 22.5: 96 h Pimephales promelas mg/L LC50 semi-static 4.06 - 5.75: 96 h Lepomis macrochirus mg/L LC50 static 7.97: 96 h Brachydanio rerio mg/L LC50 flow-through 4.2 - 4.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 22.1 - 22.8: 96 h Pimephales promelas mg/L LC50 static		
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
N-Butane 106-97-8	2.89
Sodium Lauryl Sulfate 151-21-3	1.6
Propane 74-98-6	2.3
2-Butoxyethanol 111-76-2	0.81

**Other adverse effects**

No information available

**13. Disposal Considerations**

**Waste treatment methods**

**Disposal of wastes**

Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging**

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

**14. Transport Information**

**DOT**

UN/ID no  
Proper Shipping Name  
Hazard Class

Limited Quantity  
Consumer Commodity  
ORM-D

**IATA**

**FG 438-5148-11 CHAMPION SPRAYON CARPET & UPHOLSTERY FOAMING CLEANER**

**UN/ID no** UN1950  
**Proper Shipping Name** Aerosols, flammable  
**Hazard Class** 2.1

**IMDG**

**UN/ID no** UN1950  
**Proper Shipping Name** Aerosols, flammable  
**Hazard Class** 2.1  
**Marine pollutant** This product does not contain marine pollutants.

**15. Regulatory information**

**International Inventories**

**TSCA** All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**DSL** All ingredients are listed or are excluded from listing on the DSL.

**Legend:**

TSCA - *United States Toxic Substances Control Act Section 8(b) Inventory*  
 DSL/NDSL - *Canadian Domestic Substances List/Non-Domestic Substances List*

**US Federal Regulations**

**SARA 313**

This product does not contain toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	<1	1.0

**SARA 311/312 Hazard Categories**

**Acute Health Hazard** yes  
**Chronic Health Hazard** No  
**Fire Hazard** No  
**Sudden release of pressure hazard** No  
**Reactive Hazard** No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

**US State Regulations**

**California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			X
N-Butane 106-97-8	X	X	X



**FG 438-5148-11 CHAMPION SPRAYON CARPET & UPHOLSTERY FOAMING CLEANER**

Propane 74-98-6	X	X	X
2-Butoxyethanol 111-76-2	X	X	X

**U.S. EPA Label information**

EPA Pesticide registration number Not applicable

**16. Other information**

<u>NFPA</u>	Health Hazards 2	Flammability 1	Instability 1	<b>Physical and chemical properties</b> Not applicable <b>Personal Protection</b> B - Eyes and hands protection
<u>HMIS</u>	Health Hazards 2	Flammability 2	Physical hazards 1	

Prepared by Regulatory Department  
 Issue date 09-Dec-2020  
 Revision note

This SDS supersedes a previous SDS dated January 15, 2019.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**